

MD: TS: 02/AUG'22 INTRODUCTION CIRCULAR - HERO HF DELUXE/ SPLENDOR 'i3s' - PA KIT

USHA is pleased to launch **Hero HF Deluxe/ Splendor 'i3s'** PA kit in its bi-wheeler product range.



Technical details of Hero HF Deluxe/ Splendor 'i3s' Piston and Ring set are as under:

## Piston:

Technical Data - Pist	on USHA Code→S51
Nominal Bore Diameter	50.000
Piston Diameter	49.987
Piston to Liner Clearance	00.013
Compression Height	19.200
Total Height	39.200

All dimensions are in mm

## <u>Piston Rings:</u>

Technical Data - 'HPVENT' Rings							
Ring	Ring Configuration	Axial Thickness (mm)	Closed Gap		Surface		
			(mm)	(Thou)	Treatment	Cross Section	
Тор	Inside Bevel Steel	0.80	0.10-0.25	04-10	Gas Nitriding		
Second	Taper Special Steel	0.80	0.10-0.25	04-10	Parkerising		
Oil	RIKVENT	1.50	0.20-0.70 (Rails)	08-28	Rails Chrome Plating / Parkerising		

## Cylinder Block:

Cylinder block is made of Cast Iron material, which is having good castability, machinability & superior surface finish to retain optimum amount of oil and minimize friction.

USHA piston assemblies suitable for Hero HF Deluxe/ Splendor 'i3s' are matched with superior quality Air cooled blocks & supplied as PA kits for lower oil consumption, blow-by & improved performance, in an attractive packaging.









