

SHRIRAM PISTONS & RINGS

MD: TS: 27/FEB'24

INTRODUCTION CIRCULAR - HYUNDAI SANTRO XING eRLX - PA KIT

USHA is pleased to launch '**Hyundai Santro Xing eRLX**' **single cylinder** PA Kit in its Car product range in aftermarket.



Technical details of Hyundai Santro Xing eRLX Piston and Ring set are as under:

Piston:

Technical Data - P	iston USHA Code→ C04
Nominal Bore Diameter	67.00
Piston Diameter	66.97
Piston to Liner Clearance	0.03
Compression Height	24.50
Total Height	48.50
Gudgeon Pin OD X Length	17.00 X 46.40

All dimensions are in mm

Piston Rings:

Technical Data - 'HPVENT' Rings							
	Ring	Axial	Closed Gap		Surface		
Ring	Configuration	Thickness (mm)	(mm)	(Thou)	Treatment	Cross Section	
Тор	Inside Bevel Steel (HPIBGN)	1.20	0.15-0.30	06-12	Gas Nitriding		
Second	Taper Outside Step (TOS)	1.20	0.25-0.40	10-16	Parkerising		
Oil	RIKVENT	2.00	0.20-0.70 (Rails)	08-28	Gas Nitrided Rails		

Cylinder Liner:

Cylinder liner is made from Cast Iron material using latest Centrifugal casting process having good castability, machinability and superior surface finish for better performance, minimum oil consumption, blow-by & friction etc.

Technical Data - S.F Cylinder Liner						
Parameter	Dimensions	Dimensions				
	(Inches)	(mm)				
Bore Diameter	2.6063	66.20				
Outer Diameter	2.7343	69.45				
Total Length	4.3307	110.00				
Collar Diameter	2.7579	70.05				
Collar Width	0.1929	4.90				

USHA 'Hyundai Santro Xing eRLX' piston assembly kit is supplied with quality parts for low oil consumption, blow-by & improved performance in an attractive packaging.



Shriram Pistons & Rings Ltd., 3rd Floor, Himalaya House, 23, Kasturba Gandhi Marg, New Delhi-110001 Tel: 011-46451100, 23315941, Email: tss@shrirampistons.com, Website: www.shrirampistons.com