

SHRIRAM PISTONS & RINGS LTD.

MD: TS: 12/JUL'24 INTRODUCTION CIRCULAR – MARUTI SWIFT/RITZ/D-ZIRE PETROL – PA KIT

USHA is pleased to launch 'Maruti Swift/Ritz/D-Zire Petrol' (04 Cyl.) PA Kit in its Car product range in aftermarket.



Technical details of Maruti Swift/Ritz/D-Zire Petrol piston, ring set & cylinder liner are as under:

Piston:

Technical Data – I	PistonUSHA Code \rightarrow C03		
Nominal Bore Diameter	73.00		
Piston Diameter	72.975		
Piston to Liner Clearance	0.025		
Compression Height	27.30		
Total Height	45.30		
Gudgeon Pin OD X Length	18.00 X 50.00		

All dimensions are in mm

Piston Rings:

Technical Data - 'HPVENT' Rings							
Ring	Ring Configuration	Axial	Closed Gap		Surface		
		Thickness (mm)	(mm)	(Thou)	Treatment	Cross Section	
Тор	Inside Bevel Steel (HPIBGN)	1.00	0.15-0.28	06-11	Gas Nitriding		
Second	Taper Outside Step (TOS)	1.20	0.28-0.41	11-16	Parkerising		
Oil	RIKVENT	2.00	0.20-0.50 (Rails)	08-20	Gas Nitriding		

Cylinder Liner:

Cylinder liner is made from Cast Iron material using latest Centrifugal casting process having good castability, machinability and superior surface finish for better performance, minimum oil consumption, blow-by & friction etc.

Technical Data - S.F Cylinder Liner							
Parameter	Dimensions (Inches)	Dimensions (mm)					
Bore Diameter	2.850	72.40					
Outer Diameter	2.985	75.84					
Total Length	5.000	127.00					
Collar Diameter	3.016	76.62					
Collar Width	0.183	4.65					

USHA 'Maruti Swift/Ritz/D-Zire Petrol' piston assembly along with superior quality cylinder liners & supplied as PA kits for low oil consumption, blow-by & improved performance in an attractive packaging.

