



TRACTOR RANGE - CYLINDER LINER

S.No.	Model	No. of Cyl.	Units	Bore Dia.	Outer Dia.	Total Length	Collar Dia.	Collar Thickness	SPR Part No.
1	EICHER 100 MM A/C BLOCK	2	MM	100.0000	108.8700	242.3000	113.9900	196.4000	AB-0055
			INCHES	3.9370	4.2862	9.5394	4.4878	7.7323	
2	EICHER 115 MM A/C BLOCK	1	MM	115.0000	123.0000	278.0000	121.0000	187.2000	AB-0056
			INCHES	4.5276	4.8425	10.9449	4.7638	7.3701	
3	EICHER 24 HP STD F.F	1	MM	115.0000	130.7000	281.0000	135.0000	16.0000	CL-2503
			INCHES	4.5276	5.1457	11.0630	5.3150	0.6299	
4	EICHER 24 HP (OD-5.145') F.F	1	MM	115.0000	130.6840	281.0000	135.0000	16.0000	CL-2556
			INCHES	4.5276	5.1450	11.0630	5.3150	0.6299	
5	EICHER 24 HP (OD-5.155') F.F	1	MM	114.3500	130.9380	281.0000	135.0000	16.0000	CL-2557
			INCHES	4.5276	5.1550	11.0630	5.3150	0.6299	
6	EICHER 24 HP (OD-5.165') F.F	1	MM	115.0000	131.1700	281.0000	135.0000	16.0000	CL-2558
			INCHES	4.5020	5.1642	11.0630	5.3150	0.6299	
7	EICHER 24 HP (OD-5.185') F.F	1	MM	115.0000	131.7000	281.0000	135.0000	16.0000	CL-2559
			INCHES	4.5276	5.1850	11.0630	5.3150	0.6299	
8	EICHER 312 MM A/C BLOCK	2	MM	100.0000	108.8700	236.8000	113.9900	201.9000	AB-0034
			INCHES	3.9370	4.2862	9.3228	4.4878	7.9488	
9	EICHER VALTRA STD F.F	3	MM	108.0000	123.0000	218.0000	131.7000	9.0300	CL-2299
			INCHES	4.2520	4.8425	8.5827	5.1850	0.3555	
10	EICHER XTRAC STD F.F	1	MM	115.0000	130.6700	266.5000	135.0000	16.0000	CL-2300
			INCHES	4.5276	5.1445	10.4921	5.3150	0.6299	
11	ESCORTS POWERTRACK TRUE DS+ (DIA. 95.00 MM) STD F.F	3/4	MM	95.0000	109.9400	204.0000	119.9400	11.0900	CL-0019
			INCHES	3.7402	4.3283	8.0315	4.7220	0.4366	
12	ESCORTS FT - 98 STD F.F	3/4	MM	98.0000	111.9200	204.0000	121.4000	11.0900	CL-0991
			INCHES	3.8583	4.4063	8.0315	4.7795	0.4366	
13	ESCORTS 335 STD F.F	2	MM	102.0300	116.0000	226.2500	122.6500	9.5000	CL-2252
			INCHES	4.0169	4.5669	8.9075	4.8287	0.3740	

OD- OUTER DIAMETER

O/S- OVER SIZE

CT- COLLAR THICKNESS

S.F- SEMI FINISHED

F.F- FULLY/PRE FINISHED



TRACTOR RANGE - CYLINDER LINER

S.No.	Model	No. of Cyl.	Units	Bore Dia.	Outer Dia.	Total Length	Collar Dia.	Collar Thickness	SPR Part No.
14	ESCORTS 335 F.F	2	MM	102.0300	116.0000	226.2500	122.6500	9.5000	CL-2343
			INCHES	4.0169	4.5669	8.9075	4.8287	0.3740	
15	ESCORTS 340 STD F.F	3	MM	105.0000	120.0000	216.0000	130.0000	11.1000	CL-2301
			INCHES	4.1339	4.7244	8.5039	5.1181	0.4370	
16	ESCORTS 345 STD F.F	2/3	MM	110.0000	124.0000	225.0000	130.6500	9.6500	CL-2253
			INCHES	4.3307	4.8819	8.8583	5.1437	0.3799	
17	ESCORTS 430/435 STD F.F	3	MM	91.0000	106.0000	204.3000	116.0000	11.1000	CL-2344
			INCHES	3.5827	4.1732	8.0433	4.5669	0.4370	
18	FARMTRAC 45 STD S.F	3	MM	105.5000	110.8000	209.5500	115.2500	5.0000	CL-2220
			INCHES	4.1535	4.3622	8.2500	4.5374	0.1969	
19	FORD 3000 (CT- 6.5 MM) STD S.F	3	MM	105.8000	110.8200	208.5000	112.2500	6.5000	CL-2473
			INCHES	4.1654	4.3630	8.2087	4.4193	0.2559	
20	FORD 3600 STD F.F	3	MM	106.6800	110.7800	209.5000	112.2400	4.7500	CL-2320
			INCHES	4.2000	4.3614	8.2480	4.4189	0.1870	
21	FORD 3600 (OD-4.320') S.F	3	MM	105.8000	109.7600	209.5000	110.5500	5.0000	CL-2408
			INCHES	4.1654	4.3213	8.2480	4.3524	0.1969	
22	FORD 3600 (OD-4.360') S.F	3	MM	105.8000	110.7500	209.5000	111.5500	4.7500	CL-2409
			INCHES	4.1654	4.3602	8.2480	4.3917	0.1870	
23	FORD 3600 (OD-4.362') S.F	3	MM	105.8000	110.8000	209.5000	112.2420	4.7500	CL-2410
			INCHES	4.1654	4.3622	8.2480	4.4190	0.1870	
24	FORD 3600 (OD-4.363') S.F	3	MM	105.8000	110.8200	209.5000	112.2420	4.7500	CL-2411
			INCHES	4.1654	4.3630	8.2480	4.4190	0.1870	
25	FORD 3600 (OD-4.365') S.F	3	MM	105.8000	110.8000	209.5000	112.2420	4.7500	CL-2412
			INCHES	4.1654	4.3622	8.2480	4.4190	0.1870	
26	FORD 3600 (OD-4.380') S.F	3	MM	105.8000	111.2600	209.5000	113.0600	4.7500	CL-2414
			INCHES	4.1654	4.3803	8.2480	4.4512	0.1870	

OD- OUTER DIAMETER

O/S- OVER SIZE

CT- COLLAR THICKNESS

S.F- SEMI FINISHED

F.F- FULLY/PRE FINISHED



TRACTOR RANGE - CYLINDER LINER

S.No.	Model	No. of Cyl.	Units	Bore Dia.	Outer Dia.	Total Length	Collar Dia.	Collar Thickness	SPR Part No.
27	FORD 3610 STD S.F	3	MM	110.8000	114.4300	208.5000	120.3500	2.5600	CL-2228
			INCHES	4.3622	4.5051	8.2087	4.7382	0.1008	
28	FORD 3610 MODIFIED STD S.F	3	MM	110.5000	114.4500	210.0000	115.8000	4.6300	CL-2445
			INCHES	4.3504	4.5059	8.2677	4.5591	0.1823	
29	FORD 3610 THICK COLLAR STD S.F	3	MM	110.5000	114.4300	208.3500	120.3500	4.6300	CL-2586
			INCHES	4.3504	4.5051	8.2028	4.7382	0.1823	
30	HINDUSTAN GUJRAT-453/ MAHINDRA SHAKTIMAN STD F.F	2/3	MM	102.0000	116.0000	225.7000	124.0000	10.0700	CL-2349
			INCHES	4.0157	4.5669	8.8858	4.8819	0.3965	
31	HINDUSTAN 50 STD F.F	4	MM	105.0000	120.9570	237.7000	130.0000	10.0600	CL-2278
			INCHES	4.1339	4.7621	9.3583	5.1181	0.3961	
32	INTER 434 STD F.F	4	MM	88.9000	93.6600	185.5000	101.5000	5.8000	CL-2417
			INCHES	3.5000	3.6874	7.3031	3.9961	0.2283	
33	INTER 434 CHROME HARD STD F.F	4	MM	88.9000	93.6600	185.5000	101.5000	5.8000	CL-2595
			INCHES	3.5000	3.6874	7.3031	3.9961	0.2283	
34	INTER 444 CHROME HARD STD F.F	4	MM	88.9000	97.1600	183.0000	103.3000	5.7000	CL-2596
			INCHES	3.5000	3.8252	7.2047	4.0669	0.2244	
35	INTER 444 SPECIAL STD F.F	4	MM	88.9000	97.1600	183.0000	103.3000	5.7000	CL-2597
			INCHES	3.5000	3.8252	7.2047	4.0669	0.2244	
36	INTER 444 TUFF STD F.F	4	MM	88.9000	97.1600	183.0000	103.3000	5.7000	CL-2616
			INCHES	3.5000	3.8252	7.2047	4.0669	0.2244	
37	INTER 444/ 575 DI STD F.F	4	MM	88.9000	97.1600	183.0000	103.3000	5.7000	CL-2418
			INCHES	3.5000	3.8252	7.2047	4.0669	0.2244	
38	INTER 575 DI CHROME HARD STD F.F	4	MM	88.9000	97.1600	183.0000	103.3000	5.7000	CL-2753
			INCHES	3.5000	3.8252	7.2047	4.0669	0.2244	
39	INTER 575 DI MOLY GOLD STD F.F	4	MM	88.9000	97.1600	183.0000	103.3000	5.7000	CL-2735
			INCHES	3.5000	3.8252	7.2047	4.0669	0.2244	
40	INTER 575 DI TUFF STD F.F	4	MM	88.9000	97.1600	183.0000	103.3000	5.7000	CL-2511
			INCHES	3.5000	3.8252	7.2047	4.0669	0.2244	

OD- OUTER DIAMETER

O/S- OVER SIZE

CT- COLLAR THICKNESS

S.F- SEMI FINISHED

F.F- FULLY/PRE FINISHED



TRACTOR RANGE - CYLINDER LINER

S.No.	Model	No. of Cyl.	Units	Bore Dia.	Outer Dia.	Total Length	Collar Dia.	Collar Thickness	SPR Part No.
41	INTER B-275 STD F.F	4	MM	85.7250	93.6750	179.3800	101.7000	5.8000	CL-2476
			INCHES	3.3750	3.6880	7.0622	4.0039	0.2283	
42	INTER B-275 SPECIAL STD F.F	4	MM	85.7250	93.6750	179.3800	101.7000	5.8000	CL-2645
			INCHES	3.3750	3.6880	7.0622	4.0039	0.2283	
43	INTER B-275 SPL. MOLY GOLD STD F.F	4	MM	85.7250	93.6750	179.3800	101.7000	5.8000	CL-2771
			INCHES	3.3750	3.6880	7.0622	4.0039	0.2283	
44	INTER DI LONG / YUVRAJ STD F.F	2/3/4	MM	88.9000	97.1800	181.0000	103.3000	5.7000	CL-2567
			INCHES	3.5000	3.8260	7.1260	4.0669	0.2244	
45	INTER DI CHROME HARD STD F.F	2/3	MM	88.9000	97.1800	173.0000	103.3000	5.7000	CL-2566
			INCHES	3.5000	3.8260	6.8110	4.0669	0.2244	
46	INTER DI CHROME HARD MOLY GOLD STD F.F	2/3	MM	88.9000	97.1800	173.0000	103.3000	5.7000	CL-2752
			INCHES	3.5000	3.8260	6.8110	4.0669	0.2244	
47	INTER DI MOLY GOLD STD F.F	2/3	MM	88.9000	97.1800	173.0000	103.3000	5.7000	CL-2681
			INCHES	3.5000	3.8260	6.8110	4.0669	0.2244	
48	INTER DI NITRIDED STD F.F	2/3	MM	88.9000	97.1800	173.0000	103.3000	5.7000	CL-2674
			INCHES	3.5000	3.8260	6.8110	4.0669	0.2244	
49	INTER DI NITRIDED MOLY GOLD STD F.F	2/3	MM	88.9000	97.1800	173.0000	103.3000	5.7000	CL-2780
			INCHES	3.5000	3.8260	6.8110	4.0669	0.2244	
50	JOHN DEERE 106.48 MM STD F.F	3/4/6	MM	106.4800	115.6800	197.2000	126.0000	6.9800	CL-2570
			INCHES	4.1921	4.5543	7.7638	4.9606	0.2748	
51	JOHN DEERE 106.48 MM LONG STD F.F	3/4/6	MM	106.4800	115.6800	219.0000	125.8700	6.0800	CL-2691
			INCHES	4.1921	4.5543	8.6220	4.9555	0.2394	
52	KIRLOSKAR RA100 STD F.F	1	MM	100.0000	117.0000	235.0000	129.0000	13.0000	CL-2375
			INCHES	3.9370	4.6063	9.2520	5.0787	0.5118	
53	KIRLOSKAR RA100 TUFF STD F.F	1	MM	100.0000	117.0000	235.0000	129.0000	13.0000	CL-2534
			INCHES	3.9370	4.6063	9.2520	5.0787	0.5118	
54	MAHINDRA ARJUN STD F.F	3/4	MM	94.0000	109.8800	200.1000	115.1200	9.0900	CL-2195
			INCHES	3.7008	4.3260	7.8780	4.5323	0.3579	

OD- OUTER DIAMETER

O/S- OVER SIZE

CT- COLLAR THICKNESS

S.F- SEMI FINISHED

F.F- FULLY/PRE FINISHED



TRACTOR RANGE - CYLINDER LINER

S.No.	Model	No. of Cyl.	Units	Bore Dia.	Outer Dia.	Total Length	Collar Dia.	Collar Thickness	SPR Part No.
55	MF 245 STD S.F	3	MM	90.6000	93.7000	215.7500	96.6500	3.7600	CL-2209
			INCHES	3.5669	3.6890	8.4941	3.8051	0.1480	
56	MF 245 STD F.F	3	MM	91.5500	93.7000	215.7500	96.6300	3.8100	CL-2260
			INCHES	3.6043	3.6890	8.4941	3.8043	0.1500	
57	NEW HOLLAND 3630 STD S.F	4	MM	103.3000	107.0000	198.0000	109.8500	5.0000	CL-2261
			INCHES	4.0669	4.2126	7.7953	4.3248	0.1969	
58	PERKINS P3/MF 1035 STD S.F	3	MM	88.2000	93.7350	215.9000	94.4050	4.7600	CL-2262
			INCHES	3.4724	3.6904	8.5000	3.7167	0.1874	
59	PERKINS P3/ MF 1035 STD F.F	3	MM	88.9250	93.7000	215.9000	94.4050	4.7600	CL-2392
			INCHES	3.5010	3.6890	8.5000	3.7167	0.1874	
60	PERKINS P3/ MF 1035 DI STD S.F	3	MM	88.2500	93.7200	216.0000	96.7300	3.7600	CL-2331
			INCHES	3.4744	3.6898	8.5039	3.8083	0.1480	
61	PERKINS P3/MF 1035 DI SPECIAL STD S.F	3	MM	88.2500	93.7200	216.0000	96.7300	3.7600	CL-2620
			INCHES	3.4744	3.6898	8.5039	3.8083	0.1480	
62	PERKINS P3/ MF 1035 DI (CT- 4.15 MM) STD S.F	3	MM	88.2500	93.7200	216.0000	96.7300	4.1500	CL-2683
			INCHES	3.4744	3.6898	8.5039	3.8083	0.1634	
63	PERKINS P3/ MF 1035 DI STD F.F	3	MM	88.9250	93.7000	216.0000	96.7300	3.7600	CL-2492
			INCHES	3.5010	3.6890	8.5039	3.8083	0.1480	
64	PERKINS PHASER STD S.F	4	MM	99.2000	104.2800	226.5000	107.4000	3.8400	CL-2518
			INCHES	3.9055	4.1055	8.9173	4.2283	0.1512	
65	PERKINS PHASER STD F.F	4	MM	100.0300	104.2000	226.5000	107.4000	3.8400	CL-2517
			INCHES	3.9382	4.1024	8.9173	4.2283	0.1512	
66	PERKINS PHRASER STD F.F WITH SPIGOT	4	MM	100.0000	104.2000	227.5000	107.3500	3.8500	CL-2707
			INCHES	3.9370	4.1024	8.9567	4.2264	0.1516	
67	SARTAJ STD F.F	1	MM	110.0000	125.4300	228.5000	132.8200	11.0500	CL-2212
			INCHES	4.3307	4.9382	8.9961	5.2291	0.4350	
68	SONALIKA 92 MM STD F.F	3	MM	92.0000	110.0000	211.0000	120.0000	10.0500	CL-2393
			INCHES	3.6220	4.3307	8.3071	4.7244	0.3957	

OD- OUTER DIAMETER

O/S- OVER SIZE

CT- COLLAR THICKNESS

S.F- SEMI FINISHED

F.F- FULLY/PRE FINISHED



TRACTOR RANGE - CYLINDER LINER

S.No.	Model	No. of Cyl.	Units	Bore Dia.	Outer Dia.	Total Length	Collar Dia.	Collar Thickness	SPR Part No.
69	SONALIKA 750 DI MODIFIED STD F.F	3	MM	95.0000	110.0000	211.0000	120.0000	10.0500	CL-2579
			INCHES	3.7402	4.3307	8.3071	4.7244	0.3957	
70	SONALIKA DI 750 III STD F.F	3	MM	95.0000	110.0000	211.0000	120.0000	10.0500	CL-2494
			INCHES	3.7402	4.3307	8.3071	4.7244	0.3957	
71	SONALIKA 97 MM STD F.F	3	MM	97.0000	115.9880	211.0000	123.0000	10.1000	CL-2311
			INCHES	3.8189	4.5665	8.3071	4.8425	0.3976	
72	SONALIKA 60 DI STD F.F	3	MM	100.0000	116.0000	211.0000	123.0000	10.1000	CL-2335
			INCHES	3.9370	4.5665	8.3071	4.8425	0.3976	
73	SONALIKA 102 MM STD F.F	3	MM	102.0000	116.0000	211.0000	123.0000	10.0700	CL-2334
			INCHES	4.0157	4.5669	8.3071	4.8425	0.3965	
74	SONALIKA 105 MM STD F.F	4	MM	105.0000	116.0000	211.0000	122.9500	10.0700	CL-2363
			INCHES	4.1339	4.5669	8.3071	4.8406	0.3965	
75	STANDARD 450 - 95 MM STD F.F	3	MM	95.0000	116.0000	210.0000	123.0000	10.0700	CL-2312
			INCHES	3.7402	4.5669	8.2677	4.8425	0.3965	
76	SWARAJ 724/734/735 FE TUFF STD F.F	2/3	MM	100.0000	125.4000	230.0000	128.9150	12.6000	CL-2336
			INCHES	3.9370	4.9370	9.0551	5.0754	0.4961	
77	SWARAJ 724 XM STD F.F	2/3	MM	100.0200	120.0000	216.0000	127.9500	8.2000	CL-5968
			INCHES	3.9378	4.7244	8.5039	5.0374	0.3228	
78	SWARAJ 735 XM STD F.F	2/3	MM	100.0000	117.0000	215.0000	129.0000	12.6000	CL-5965
			INCHES	3.9370	4.6063	8.4646	5.0787	0.4961	
79	SWARAJ 855 FE STD F.F	2/3/ 4/6	MM	110.0000	125.4000	230.0000	132.8500	10.5000	CL-2314
			INCHES	4.3307	4.9370	9.0551	5.2303	0.4134	
80	SWARAJ 744 FE/ KIRLOSKAR RB-110 STD F.F	1	MM	110.0000	125.4000	230.0000	132.9150	11.2000	CL-2419
			INCHES	4.3307	4.9370	9.0551	5.2329	0.4409	
81	SWARAJ 120MM STD F.F	1	MM	120.0000	138.8800	239.0000	149.9000	12.5700	CL-2313
			INCHES	4.7244	5.4677	9.4094	5.9016	0.4949	

OD- OUTER DIAMETER

O/S- OVER SIZE

CT- COLLAR THICKNESS

S.F- SEMI FINISHED

F.F- FULLY/PRE FINISHED



TRACTOR RANGE - CYLINDER LINER

S.No.	Model	No. of Cyl.	Units	Bore Dia.	Outer Dia.	Total Length	Collar Dia.	Collar Thickness	SPR Part No.
82	ZETOR 2511 STD F.F	2/3/4	MM	95.0000	111.0000	210.5000	121.8500	10.0600	CL-2238
			INCHES	3.7402	4.3701	8.2874	4.7972	0.3961	
83	ZETOR 2511 SPECIAL STD F.F	2/3/4	MM	95.0000	111.0000	210.5000	121.8500	10.0600	CL-2399
			INCHES	3.7402	4.3701	8.2874	4.7972	0.3961	
84	ZETOR 2522 STD F.F	2/3	MM	95.0000	110.0000	211.0000	120.0000	10.1000	CL-2239
			INCHES	3.7402	4.3307	8.3071	4.7244	0.3976	
85	ZETOR 2522 SPECIAL STD F.F	2/3	MM	95.0000	110.0000	211.0000	120.0000	10.1000	CL-2400
			INCHES	3.7402	4.3307	8.3071	4.7244	0.3976	
86	ZETOR 2911 STD F.F	2	MM	100.0000	111.0000	210.5000	121.8000	10.0600	CL-2240
			INCHES	3.9370	4.3701	8.2874	4.7953	0.3961	
87	ZETOR 2911 SPECIAL STD F.F	2	MM	100.0000	111.0000	210.5000	121.8000	10.0600	CL-2401
			INCHES	3.9370	4.3701	8.2874	4.7953	0.3961	
88	ZETOR 5911 STD F.F	4	MM	100.0000	115.0000	225.5000	122.9000	10.0600	CL-2243
			INCHES	3.9370	4.5276	8.8780	4.8386	0.3961	
89	ZETOR 5911 SPECIAL STD F.F	4	MM	100.0000	115.0000	225.5000	122.9000	10.0600	CL-2403
			INCHES	3.9370	4.5276	8.8780	4.8386	0.3961	
90	ZETOR 4511 STD F.F	3	MM	102.0000	116.0000	225.5000	123.0000	10.0700	CL-2241
			INCHES	4.0157	4.5669	8.8780	4.8425	0.3965	
91	ZETOR 4511 SPECIAL STD F.F	3	MM	102.0000	116.0000	225.5000	123.0000	10.0700	CL-2402
			INCHES	4.0157	4.5669	8.8780	4.8425	0.3965	
92	ZETOR 4922 STD F.F	3	MM	102.0000	116.0000	211.0000	123.0000	10.1000	CL-2242
			INCHES	4.0157	4.5669	8.3071	4.8425	0.3976	
93	ZETOR 6911 SPECIAL STD F.F	4	MM	102.0000	115.0000	225.5000	122.9000	10.0600	CL-2244
			INCHES	4.0157	4.5276	8.8780	4.8386	0.3961	
94	ZETOR 7511 STD F.F	4	MM	105.0000	120.0000	215.9000	127.9200	8.0700	CL-2245
			INCHES	4.1339	4.7244	8.5000	5.0362	0.3177	
95	ZETOR 7511 PHOSPHATED STD F.F	4	MM	105.0000	120.0000	215.9000	127.9200	8.0700	CL-2609
			INCHES	4.1339	4.7244	8.5000	5.0362	0.3177	

OD- OUTER DIAMETER

O/S- OVER SIZE

CT- COLLAR THICKNESS

S.F- SEMI FINISHED

F.F- FULLY/PRE FINISHED



HAND TRACTOR/ TILLER/ INDUSTRIAL/OFF ROAD APPLICATIONS - CYLINDER LINER

S.No.	Model	No. of Cyl.	Units	Bore Dia.	Outer Dia.	Total Length	Collar Dia.	Collar Thickness	SPR Part No.
1	ARJUN SINGLE CYLINDER STD F.F	1	MM	127.0000	143.6400	255.0000	147.7800	19.0000	CL-2214
			INCHES	5.0000	5.6551	10.0394	5.8181	0.7480	
2	ESCORTS JCB STD F.F	3	MM	110.0000	125.4000	230.0000	132.8500	10.5000	CL-2254
			INCHES	4.3307	4.9370	9.0551	5.2303	0.4134	
3	KIRLOSKAR R1040 STD F.F	4	MM	105.0000	120.0000	215.9000	127.9200	8.0700	CL-2322
			INCHES	4.1339	4.7244	8.5000	5.0362	0.3177	
4	KIRLOSKAR R1040 PHOSPHATED STD F.F	4	MM	105.0000	120.0000	215.9000	127.9200	8.0700	CL-2682
			INCHES	4.1339	4.7244	8.5000	5.0362	0.3177	
5	JCB 3DX (103 MM) STD S.F	1	MM	102.2000	106.0800	227.0000	109.0000	4.9000	CL-2374
			INCHES	4.0236	4.1764	8.9370	4.2913	0.1929	
6	JCB 4DX (105 MM) STD S.F	1	MM	104.2000	109.7800	235.0000	110.5000	6.0000	CL-2447
			INCHES	4.1024	4.3220	9.2520	4.3504	0.2362	
7	KUBOTA 95 IDI STD F.F	1	MM	95.0000	109.9000	187.5000	116.8000	10.1000	CL-2206
			INCHES	3.7402	4.3268	7.3819	4.5984	0.3976	
8	KUBOTA 95 IDI (OD O/S- 0.002') S.F	1	MM	94.9500	109.9000	187.5000	116.8000	10.1000	CL-2376
			INCHES	3.7382	4.3268	7.3819	4.5984	0.3976	
9	KUBOTA 95 IDI (OD O/S- 0.003') S.F	1	MM	94.9200	109.9000	187.5000	116.8000	10.1000	CL-2377
			INCHES	3.7370	4.3268	7.3819	4.5984	0.3976	
10	KUBOTA 95 IDI (OD O/S-0.005') S.F	1	MM	94.8700	109.9000	187.5000	116.8000	10.1000	CL-2378
			INCHES	3.7350	4.3268	7.3819	4.5984	0.3976	
11	KUBOTA 95 DI STD F.F	1	MM	95.0000	109.9000	190.4000	116.8000	10.1000	CL-2281
			INCHES	3.7402	4.3268	7.4961	4.5984	0.3976	
12	MAHINDRA 235 DI (1 CYLINDER) STD F.F	1	MM	127.0000	143.6400	254.9500	147.7800	19.0000	CL-2348
			INCHES	5.0000	5.6551	10.0374	5.8181	0.7480	
13	POWER TILLER SHB 105 MM STD F.F	1	MM	105.0000	118.4800	205.6000	123.7500	10.0300	CL-2493
			INCHES	4.1339	4.6646	8.0945	4.8720	0.3949	
14	POWER TILLER 110 MM STD F.F	1	MM	110.0000	124.0000	213.0000	130.8500	9.0600	CL-2461
			INCHES	4.3307	4.8819	8.3858	5.1516	0.3567	

OD- OUTER DIAMETER

O/S- OVER SIZE

CT- COLLAR THICKNESS

S.F- SEMI FINISHED

F.F- FULLY/PRE FINISHED



HAND TRACTOR/ TILLER/ INDUSTRIAL/OFF ROAD APPLICATIONS - CYLINDER LINER

S.No.	Model	No. of Cyl.	Units	Bore Dia.	Outer Dia.	Total Length	Collar Dia.	Collar Thickness	SPR Part No.
15	POWER TILLER 110 MM (KOLKATA TYPE) STD F.F	1	MM	110.0000	128.9000	212.0000	134.8000	9.1000	CL-2654
			INCHES	4.3307	5.0748	8.3465	5.3071	0.3583	
16	POWER TILLER 110 MM (PUNJAB TYPE) STD F.F	1	MM	110.0000	128.9000	205.4000	134.8500	9.0600	CL-2544
			INCHES	4.3307	5.0748	8.0866	5.3091	0.3567	
17	VST POWER TILLER (SHAKTI 120 -92 MM) STD F.F	1	MM	92.0000	105.0000	170.0000	111.4500	8.0500	CL-2368
			INCHES	3.6220	4.1339	6.6929	4.3878	0.3169	
18	VST POWER TILLER (SHAKTI 130/135 DI - 95 MM) STD F.F	1	MM	95.0000	106.8800	170.0000	113.7200	8.0600	CL-2369
			INCHES	3.7402	4.2079	6.6929	4.4772	0.3173	
19	DONFING 100 MM STD F.F	1	MM	100.0000	113.9000	204.4000	120.7000	10.0000	CL-2298
			INCHES	3.9370	4.4843	8.0472	4.7520	0.3937	
20	SARACHI 95 MM (2 'O' RING) STD F.F	1	MM	95.0000	109.9600	210.0000	117.8500	10.0200	CL-2430
			INCHES	3.7402	4.3291	8.2677	4.6398	0.3945	
21	SARACHI 100 MM STD F.F	1	MM	100.0200	111.9700	210.0000	121.8200	8.8500	CL-2310
			INCHES	3.9378	4.4083	8.2677	4.7961	0.3484	
22	SYFING 95 MM STD F.F	1	MM	95.0000	109.8800	209.5000	117.9000	10.0000	CL-2290
			INCHES	3.7402	4.3260	8.2480	4.6417	0.3937	
23	TEXMO 94 MM STD F.F	1	MM	94.0000	105.9500	157.0000	114.0500	10.0800	CL-2225
			INCHES	3.7008	4.1713	6.1811	4.4902	0.3969	
<p>OD- OUTER DIAMETER O/S- OVER SIZE CT- COLLAR THICKNESS S.F- SEMI FINISHED F.F- FULLY/PRE FINISHED</p>									