

SHRIRAM PISTONS & RINGS LTD.

MD: TS: 47/JAN'25

INTRODUCTION CIRCULAR - HONDA DREAM YUGA/ NEO/ LIVO- PA KIT

USHA is pleased to launch **HONDA DREAM YUGA/ NEO/ LIVO** PA kit in its aftermarket bi-wheeler product range.



Technical details of HONDA DREAM YUGA/ NEO/ LIVO Piston and Ring set are as under:

Piston:

Technical Data – P	on USHA Code→ NC\$38		
Nominal Bore Diameter	50.00		
Piston Diameter	49.988		
Piston to Liner Clearance	0.012		
Compression Height	17.90		
Total Height	36.90		
Gudgeon Pin Length X OD	33.00 X 12.00		

All dimensions are in mm

Piston Rings:

Technical Data - 'HPVENT' Rings							
Ring	Ring Configuration	Axial Thickness (mm)	Closed (mm)	Gap (Thou)	Surface Treatment	Cross Section	
Тор	Steel Inside Bevel (HPIBCR)	0.80	0.10-0.25	04-10	Chrome Plating/ Parkerising		
2 nd	Special Steel Taper (TSS)	0.80	0.10-0.25	04-10	Parkerising		
Oil	RIKVENT	1.50	0.20-0.70 (Rails)	08-28	Chrome Plated Rails/ Parkerising		

Cylinder Block:

Cylinder block is manufactured using Aluminium alloy which is light weight and has better thermal conductivity resulting in improved engine efficiency.

USHA piston assemblies suitable for 'HONDA DREAM YUGA/ NEO/ LIVO' are matched with these superior quality air cooled blocks for supply as PA kits for low oil consumption & improved performance in an attractive packaging.







Technical Product News is an exclusive update of product & information from

Shriram Pistons & Rings Ltd., 3rd Floor, Himalaya House, 23, Kasturba Gandhi Marg, New Delhi-110001

Tel: 011-46451100, 23315941, Email: tss@shrirampistons.com, Website: www.shrirampistons.com